



HV(中高电压薄膜电容器)

Middle-High Voltage Film Capacitor

SPECIFICATIONS

Rated voltage: 10kVDC,12kVDC,15kVDC

Capacitance range:100-1000pF

Capacitance tolerance: $\pm 5\%$, $\pm 10\%$

Operating temperature: $-40^{\circ}\text{C} \sim +100^{\circ}\text{C}$

Dissipation Factor:1kHz $\pm 20\%$



FEATURES

1. Another new product available in voltage rating from 10~15kVDC
2. Capacitance from 100~1000pF
3. Optimum choice for double voltage rectification in display.TV receivers and other circuits.

Allowed Temperature	Rated Voltage(kVDC)	Capacitance(pF)	Dimensions(mm)			
			w	T	H	P
$\pm 100^{\circ}\text{C}$	10,0	100	10,5	5,0	10,0	8,0
	—	250	13,5	5,0	11,0	10,0
	—	500	14,5	5,5	13,0	10,0
	—	750	15,5	7,0	13,0	12,0
	—	1000	15,5	7,0	15,0	12,0
	12,0	100	13,5	4,5	13,0	10,0
	—	250	14,0	5,5	13,0	10,0
	—	500	15,0	6,0	15,0	11,0
	—	750	14,5	6,0	18,0	10,0
	—	1000	16,0	7,5	18,0	12,0
	15,0	100	13,5	4,5	13,0	10,0
	—	250	14,5	5,5	13,0	10,0
	—	500	16,0	7,0	15,0	12,0
	—	750	16,0	7,0	18,0	12,0
	—	1000	16,8	8,0	18,5	12,0

<http://www.stcapacitors.com>